



Key Type Drill Chucks

TYPE:G



- Representative products, super precision durable & rigity
- Big outside diameter suit for heary duty
- The nut and jaws adopt AISI-52100 (bearing steel) and heat-treated, durability the precision can be lssted.
- The taper is precision ground, advance the precision.
- Auuracy: 90mm length within 0.08mm

ORDER NO.	Type	Clamping Capacity mm inch	Female Taper DIN or jacobcs	OUTER ∅ mm	Length		Wt g	Key Size	QTY Pcs./ Cu-Ft	N.W/G.W kgs	CODE NO.
					open B mm	closed A mm					
10006	G-6H	0.5-6.5	J1	32	40	50	200	CK3	100/0.82	20/21	3303-001
10007		1/64"-1/4"	B10	32	40	50	200	CK3	100/0.82	20/21	3303-002
10017	G-10XH	0.5-10	J2	41.5	50.5	64	390	CK4	60/0.85	24/25	3303-003
10018		1/64"-3/8"	J2S	41.5	50.5	64	390	CK4	60/0.85	24/25	3303-004
10050	G-13XH	0.5-13 1/64"-1/2"	J6	56	69	82	800	P6	36/0.83	30/31	3303-006
10051			B16	56	69	82	800	P6	36/0.83	30/31	3303-007
10052			J33	56	69	82	800	P6	36/0.83	30/31	3303-008
10068	G-16XH	1-16	J3	65	78	96	1000	P7	24/0.84	24/25	3303-009
10070		1/32"-5/8"	B18	65	78	96	1000	P7	24/0.84	24/25	3303-010
10074	G-19XH	3-19	J4	74	89	126	2150	P7	18/0.83	39/40	3303-011
10075		1/8"-3/4"	B22	74	89	126	2150	P7	18.0.83	39/40	3303-012



Ball Bearing Key Tpye Super Chucks

TYPE:H



- Suitable for heavy duty drilling use.
- By using anti-thrust bearing to increase the gripping power, so that, high speed drilling. can be performed
- All parts hardened by heat treatment and precision ground precision can be lasted, super clamping power.
- Accuracy:100m/m length is within 0.08m/m

ORDER NO.	Type	Clamping Capacity mm inch	Female Taper DIN or jacobcs	OUTER ∅ mm	Length		Wt g	Key Size	CODE NO.
					open B mm	closed A mm			
12011	10BXH	1-10 1/32"-3/8"	J2S	45	56	64	390	P4	3303-030
12006	13BXH	1-13 1/32"-1/2"	J3	62	75	95	1200	P6	3303-031
12001			J6						
12002			J33						
12003	16BXH	1-16 1/32"5/8"	J3	65	81	101	1500	P7	3303-034
12004			B18						
12005	19BXH	1-19 1/32"-3/4"	J4	74	100	130	2150	P7	3303-036
12007	25BXH	5-25 3/16"-1"	J5	93	112	153	4100	T9	3303-037