





Radial Drilling And Milling Heads-Back ward Type TYPE DIN 1809



MODE: BL

LEFT-HAND



MODE: BR

RIGHT-HAND



- External coolant supply
- Collet is not included.
- To be used for collet DIN 6499

DIMENSIONS

Order No.	D DIN 69880	X Capacity	S	Maximum R.P.M.	i	A	B	C	E	F	G	M	CODE NO.
BR2018091657 BL2018091657	20	1-10 ER16	32	5000	1:1	80	50	43	62.5	27	28.5	57	5006-015
BR3018092569 BL3018092569	30	1-16 ER25	42	5000	1:1	95	60	41.5	75.5	31.5	29	69	5006-016
BR4018093290 BL4018093290	40	2-20 ER32	50	5000	1:1	124	80	44	110	42	34	90	5006-017
BR5018094090 BL5018094090	50	3-26 ER40	62	5000	1:1	129	86	49	112	45	39	90	5006-018
BR60180950102 BL60180950102	60	10-34 ER50	78	5000	1:1	147	104	83	118	54	42	102	5006-019

Radial Tapping Heads-Back ward Type DIN 1809

DIMENSIONS



Order No.	D DIN 69880	X Capacity	S	Maximum R.P.M.	i	A	B	C	E	F	G	M	CODE NO.
TBR3018091669 TBL3018091669	30	1-10 ER16	32	3000	1:1	95	60	44	75.5	31.5	32	69	5006-020
TBR4018092090 TBL4018092090	40	1-13 ER20	35	3000	1:1	124	80	50	110	42	34	90	5006-021
TBR5018092590 TBL5018092590	50	1-16 ER25	42	3000	1:1	129	86	54	112	45	36	90	5006-022
TBR60180932102 TBL60180932102	60	2-20 ER32	50	3000	1:1	147	104	87	118	54	40	102	5006-023



Radial Drilling And Milling Heads TYPE DIN 1809



MODE: FL

LEFT-HAND



MODE: FR

RIGHT-HAND



- To be used for collet DIN 6499
- Collet is not included.
- External coolant supply

DIMENSIONS

Order No.	D DIN 69880	X Capacity	S	Maximum R.P.M.	i	A	B	C	F	G	M	CODE NO.
FR3018092555 FL3018092555	30	1-16 ER25	42	5000	1:1	87	64	74.5	41	26	55	5006-024
FR4018093265 FL4018093265	40	2-20 ER32	50	5000	1:1	99	80	71	40	23	65	5006-025
FR5018094075 FL5018094075	50	3-26 ER40	63	5000	1:1	115	88	103	56	40	75	5006-026

Radial Tapping Heads DIN 1809

DIMENSIONS

Order No.	D DIN 69880	X Capacity	S	Maximum R.P.M.	i	A	B	C	F	G	M	CODE NO.
TFR3018092555 TFL3018092555	30	1-10 ER16	32	3000	1:1	87	64	75	41	30	55	5006-027
TFR4018093265 TFL4018093265	40	1-13 ER20	35	3000	1:1	99	80	70	40	25	65	5006-028
TFR5018094075 TFL5018094075	50	1-16 ER25	42	3000	1:1	115	88	103	56	42	75	5006-029