



Drilling Head Units

DH-TYPE



WHEN YOU ORDER, YOU MUST CONFIRM

1. THE SPINDLE SIZE (JT-6, ER- OR MT-3)
2. 3PH MOTOR AND POWER, VOLTAGE & PHASE
3. THE MATERIAL OF WORKPIECE
4. THE MATERIAL AND DIA. OF CUTTING TOOL
5. THE TRAVEL POWER ON MACHINE IS HYDRAULIC OR AIR.
6. FIXED PRM.

SPECIFICATION

ORDER NO.	TRAVEL	CAPACITY	MAX. RPM	POWER	CENTER HEIGHT	MOTOR	HYDRAULIC SPACE	WEIGHT kgs	CODE NO.
DH3 - 60M	60 m/m	6 ϕ	10000	HYDRAULIC OR AIR	50 \pm 0.02	1/2 HP	12.6 cm ²	26 kg	7002-700
DH5 - 85M	85 m/m	13 ϕ	5000	HYDRAULIC OR AIR	70 \pm 0.02	1 HP	21.6 cm ²	50 kg	7002-701
DH6 - 130M	130 m/m	16 ϕ	3200	HYDRAULIC	70 \pm 0.02	1 HP	43.2 cm ²	45 kg	7002-702
DH8 - 150M	150 m/m	25 ϕ	1500	HYDRAULIC	90 \pm 0.02	2 HP	71.2 cm ²	70 kg	7002-703
DH9 - 150M	150 m/m	35 ϕ	1200	HYDRAULIC	90 \pm 0.02	2 HP	71.2 cm ²	75 kg	7002-704

DRILLING HEAD UNITS DH3 - 60M

