



# Tapping Head Units



## WHEN YOU ORDER, PLEASE CONFIRM

1. ORDER NO.
2. Spindle Size (JT-2, JT-6, ER-16, ER-20, MT-2, MT-3, MT-4, NT-40, TR-20)
3. Tap Size And Pitch.
4. Voltage Number of Phase, Frequency.
5. Fixed R. P. M.
6. If Spindle Revolve Under 400 RPM  
Use Reducer Gear Motor (Option).

ORDER NO.	SPINDLE STROKE	CAPACITY (S45C)	MIN. PITCH	SPINDLE CENTER	MOTOR	WEIGHT kgs.	CODE NO.
TH-50M	50 m/m	6 $\varnothing$	0.4 m/m	50 <sup>m</sup> / <sub>m</sub> ± 0.02	1/2 HP	18kg	7002-801
TH-65M	65 m/m	14 $\varnothing$	0.6 m/m	70 <sup>m</sup> / <sub>m</sub> ± 0.02	1 HP	30kg	7002-802
TH-85M	85 m/m	35 $\varnothing$	0.6 m/m	90 <sup>m</sup> / <sub>m</sub> ± 0.02	2 HP	70kg	7002-803
TH-90M	90 m/m	45 $\varnothing$	0.6 m/m	90 <sup>m</sup> / <sub>m</sub> ± 0.02	2 HP	80kg	7002-804